## PA COLUMN SPEAKERS











RCM-15T

15W



RCM-10T





Models available: RCM-20, RCM-15, RCM-10 (With  $\Omega$  & 100V Strip)

## Features:

30W

RCM-30T

- Designed for all kinds of applications Indoor and Outdoor
- Foam layer provided to protect speakers from dust etc.
- Metal Chesis & Grill makes the speaker column withstand hard weather conditions
- Wall mounting clamps supplied for ease in installation
- Ideal for Auditoriums, Halls, Worship Places, Railway Plateform, Workshops etc.

## Available in Two Versions:

A. With 100V Line: Models- RCM-30T, RCM-20T, RCM-15T, RCM-10T (Available in Grey Color)

B. With Low Impedance Taps & 100V Line: Models-RCM-20, RCM-15, RCM-10 (Available in Off White Color)



SPECIFICATIONS	RCM-30T	RCM-20/ RCM-20T	RCM-15/ RCM-15T	RCM-10/ RCM-10T
INPUT POWER	20W RMS	15W RMS	10W RMS	5W RMS
	30W Max.	20W Max.	15W Max.	10W Max.
POWER TAPS	10W/15W/20W	7.5W/10W/15W	5W/7.5W/10W	5W/7.5/10W
VOLTAGE	100W	100V	100V	100V
*IMPEDANCE	-	8Ω	8Ω	4Ω
FREQ. RESPONSE	150Hz - 10,000Hz	150Hz - 10,000Hz	150Hz - 10,000Hz	150Hz - 10,000Hz
SPL at 1W/1m	110 dB	107 dB	103 dB	100 dB
No. OF SPEAKERS	4 x 6"*4"	3 x 6"*4"	2 x 6"*4"	1 x 6"*4"
DIMENSIONS	165W x 145D x 880H mm	165W x 145D x 660H mm	165W x 145D x 455H mm	165W x 145D x 228H mm
WEIGHT	7.000 Kg	4.500 Kg	4.000 Kg	2.500 Kg
MATERIAL	METAL	METAL	METAL	METAL

<sup>\*</sup>Only available in Low impedance Tap/100V Line models - RCM-20, RCM-15, RCM-10

<sup>\*</sup>Technical specifications are estimates.

<sup>\*</sup>Design & specification subject to change without notice.